Machine Learning: Closing

Hao Tang

March 28, 2025

A model is an imaginary artifact that describes the inner working of something.

A model is an imaginary artifact that describes the inner working of something.


imaginary


A model is an imaginary artifact that describes the inner working of something.


- imaginary
- describes inner working

A model is an imaginary artifact that describes the inner working of something.

- imaginary
- describes inner working
- of something







The hypothesis class \mathcal{H} is PAC learnable with an algorithm A if for any distribution \mathcal{D} , $\epsilon > 0$, and $0 < \delta < 1$, there exists N such that

$$\mathbb{P}_{S \sim \mathcal{D}^n} \Big[L_{\mathcal{D}}(A(S)) - \min_{h \in \mathcal{H}} L_{\mathcal{D}}(h) > \epsilon \Big] < \delta \tag{1}$$

for any $n \geq N$.

Perceptrons

- Perceptrons
- Linear classifiers

- Perceptrons
- Linear classifiers
- Gaussian mixture models

- Perceptrons
- Linear classifiers
- Gaussian mixture models
- Transformers

• Machine learning does not eliminate the need to build models.

- Machine learning does not eliminate the need to build models.
- What is machine learning?

- Machine learning does not eliminate the need to build models.
- What is machine learning?
- When to use machine learning?

- Machine learning does not eliminate the need to build models.
- What is machine learning?
- When to use machine learning?
- How to use machine learning?

Types of thinking

- Mathematical
 - What happens if we have the optimal solution?
- Computational
 - What are the exact steps?
- Statistical
 - How many samples do we need?

Connections to other courses

- Foundations of Data Science (FDS)
- Applied Machine Learning (AML)
- Machine Learning and Pattern Recognition (MLPR)
- Probabilistic Modeling and Reasoning (PMR)
- Machine Learning Practical (MLP)
- Machine Learning Theory (MLT)
- Reinforcement learning (RL)

Connections to other courses

- Foundations of natural language processing (FNLP)
- Accelerated natural language processing (ANLP)
- Natural language understanding, generation, and machine translation (NLU+)
- Speech processing (in PPLS)
- Automatic speech recognition (ASR)
- Speech synthesis (in PPLS)
- Computer vision
- Advanced robotics
- Machine learning systems

Tasks we haven't talked about

- Information retrieval
- 3D reconstruction
- Text generation
- Protein folding

Evaluation we haven't talked about

- Mean average precision
- Receiver operating characteristic (ROC) curve
- Word error rates (WER)
- Bilingual evaluation understudy (BLEU) score
- Mean opinion score (MOS)

Techniques we haven't talked about

- More optimization
 - There are a lot of problems that cannot be solved with gradient descent.
- k nearest neighbor
 - A point is like its neighbors.
- Decision trees
 - Decisions are based on conditional statements.
- More dimensionality reduction
 - Points in space have structures.
- Bayesian approaches
 - Beliefs are updated and marginalized.

- Active learning
 - What is the next sample that is most useful to learn?

- Active learning
 - What is the next sample that is most useful to learn?
- Online learning
 - What can we learn if we make decisions sequentially and can look back?

- Active learning
 - What is the next sample that is most useful to learn?
- Online learning
 - What can we learn if we make decisions sequentially and can look back?
- Semi-supervised learning
 - What do we do with unlabeled data?

- Active learning
 - What is the next sample that is most useful to learn?
- Online learning
 - What can we learn if we make decisions sequentially and can look back?
- Semi-supervised learning
 - What do we do with unlabeled data?
- Federated learning
 - Can learning be distributed?

Aspects

- Privacy
- Fairness
- Interpretability

Differentially private

A learning algorithm A is differentially private if for all data sets S and S^i that differs in the i-th sample,

$$\mathbb{P}[A(S) \in \mathcal{G}] < e^{\epsilon} \mathbb{P}[A(S^i) \in \mathcal{G}] + \delta$$
 (2)

for any subset $\mathcal{G}\subseteq\mathcal{H}$ of hypothesis.

Fairness

- An outcome Y should be independent of groups G. $(Y \perp G)$
- A score R should be independent of the groups G given the outcome Y.
 (R ⊥ G|Y)
- An outcome Y should be independent of the groups G given the score R.
 (Y ⊥ G|R)

Artificial Intelligence

Artificial Intelligence

- Building models of intelligence, not solving tasks
- Involving philosophy, psychology, linguistics, etc

What we have learned in this course

What we have learned in this course

- Formalize a ML problem with math
- Read and understand ML theorems
- Turn ML algorithms into programs